

DECLARATION ON THE PROPERTIES OF CONSTRUCTION MATERIALS No. 2013/004

in accordance with the Regulation of the European Parliament, and the Council of the EU No. 305/2011 of 9th March 2011, which lays down the harmonized conditions for the sale of construction products and materials on the market.

1. The unique identification code of the product type:
DKM-CPR-2013/004

2. Type, batch or serial number, or any other distinguishing feature enabling identification of the construction product:
DEKCASSETTE LE

3. Intended use of the construction product is in accordance with the relevant harmonized technical specification:
self supporting cassettes for claddings installed on supporting grids or supporting structures of civil, office and industrial buildings

For more information on how to use this product, please see: www.dekmetal.com

4. Name, company or registered trade mark and contact address of the manufacturer:
DEKMETAL s.r.o.
Tiskařská 10/257
108 28 Praha 10, ČR

6. The system, or systems, for the assessment and verification of the constancy of performance of this construction

System 3

7. For the purpose of reporting on the properties of a construction product which is covered by the harmonised standards:

The manufacturer has performed the initial tests on the product type, reaction to fire tests carried out by the notified subject number. 0679, CSTB, 84 AVENUE JEAN JAURES, 77447 MARNE-LA-VALLEE CEDEX 2, FRANCE a SNAS 041/S-159, FIRES s.r.o., Osloboditelov 282, 059 35 Batizovce, Slovak Republic as well as operating a system of production management.

9. Product Properties given in the Declaration:

Basic Characteristics	Properties	Harmonised Technical Specifications:
Water Resistance	Complies with Specifications	EN 14782
Dimensional Changes (steel)	$12 \times 10^{-6} K^{-1}$	
Release of Dangerous Materials	Does not Contain Dangerous Materials	
Reaction to Fire	A1	
Durability – material + metallic layer	DX51D+Z275, S250GD+Z275, S280GD+Z275, S320GD+Z275	
Durability – organic layer	Side 1: SP25µm, SP35µm, PU50µm / Side 2: SP25µm, SP7µm	
Durability - Thickness	0,50mm; 0,63mm; 0,75mm; 0,88mm; 1,00mm; 1,20mm	

10. The properties of the product are specified in points No. 1 and 2, and are in compliance with the specifications given in point No. 9. This declaration on the properties of the construction product is issued under the sole responsibility of the manufacturer referred to in paragraph No. 4. Signed for, and on behalf, of the manufacturer:

Prague - 01-07-2013



Ing. Jiří Bracháček
Executive director